

6 MP Optical Explosion-Proof Camera



SeSys's ATEX and IECEx compliant digital cameras are designed to facilitate remote monitoring of inhospitable, hazardous or explosive areas reducing the dangers posed to personnel.

Light sensitive, high-resolution sensors make these IP-based cameras perfect for operational, health and safety and security requirements.

Professional Hazardous Area Optical Camera

■ Optical Lens Explosion-Proof Camera For Indoor and Outdoor use

Single independent 6 MP sensor option

■ Modular System For Maximum Flexibility

Exchangable lens with horizontal image angles from 15° to 103°

■ Minimum Installation Requirement

Single cable for camera data and power

■ Reduced Energy Costs

Power consumption < 7 Watt, standard PoE IEEE 802.3af

■ Virtually Maintenance-Free

No moving parts reduces camera maintenance and down-time





6 MP Optical Explosion-Proof Camera

TECHNICAL SPECIFICATION															
ATEX / IECEx Certificate	II2 G Ex db op pr IIC Gb T6 / II 2 D Ex tb IIIC T85°C Db IP66/IP67														
Lens Options	B036 (103° x 77°), B041 (90° x 67°), B061 (60° x 45°), B079 (45° x 34°), B119 (31° x 23°), B237 (15° x 11°)														
Light Sensitivity	Colour: 0.1 lux (t=1/60 s), 0.005 lux (t=1/1 s) / B/W: 0.02 lux (t=1/60 s), 0.001 lux (t=1/1 s)														
Image Sensors	1/1.8" CMOS, 6MP (3072 x 2048), Progressive Scan														
Microprocessor	i.MX 6 Dual Core incl. GPU (1GB RAM, 512 MB Flash)														
Max. Frame Rate (fps) (only single core used)	MxPEG: 42@HD (1280 x 720), 34@Full-HD (1920 x 1080), 24@QXGA (2048 x 1536), 15@5MP, 12@6MP & 6@2x6MP MJPEG: 26@HD (1280 x 720), 13@Full-HD (1920 x 1080), 9@QXGA (2048 x 1536), 5@5MP, 4@6MP & 2@2x6MP H.264: 25@Full-HD (1920 x 1080), 20@QXGA (2048 x 1536)														
Available Video Codec	MxPEG / MJPEG / H.264 - bandwidth limitation available, output image format up to QXGA (2048 x 1536)														
Internal DVR, ex works	4GB MicroSD slot (upgradable) - encrypted recording														
External DVR	Support for recording to network-attached storage (NAS), different streams for live image and recording, MxFFS with archive function, pre-alarm and post-alarm images, monitoring recording with failure reporting														
Video Management Software (VMS)	MxManagement Centre / MOBOTIX App for iOS and Android devices / Web Browser														
General Functions	<table border="0"> <tr> <td>Multistreaming</td> <td>Multicast stream via RTSP</td> </tr> <tr> <td>Digital zoom and pan</td> <td>Video motion detector</td> </tr> <tr> <td>MxActivitySensor</td> <td>Privacy masking</td> </tr> <tr> <td>ONVIF Profile S supported</td> <td>Programmable exposure zones</td> </tr> <tr> <td>Snapshot recording (pre/post-alarm images)</td> <td>Time controlled flexible event logic</td> </tr> <tr> <td>Weekly schedules for recordings/actions</td> <td>Event video and image transfer via FTP and email</td> </tr> <tr> <td>Programming interface (HTTP-API)</td> <td></td> </tr> </table>	Multistreaming	Multicast stream via RTSP	Digital zoom and pan	Video motion detector	MxActivitySensor	Privacy masking	ONVIF Profile S supported	Programmable exposure zones	Snapshot recording (pre/post-alarm images)	Time controlled flexible event logic	Weekly schedules for recordings/actions	Event video and image transfer via FTP and email	Programming interface (HTTP-API)	
Multistreaming	Multicast stream via RTSP														
Digital zoom and pan	Video motion detector														
MxActivitySensor	Privacy masking														
ONVIF Profile S supported	Programmable exposure zones														
Snapshot recording (pre/post-alarm images)	Time controlled flexible event logic														
Weekly schedules for recordings/actions	Event video and image transfer via FTP and email														
Programming interface (HTTP-API)															
Security	User and group management / SSL connections / IP-based access control / IEEE 802.1x / Intrusion detection / Digital image signature														
Protocols	IPv4, IPv6, HTTP, HTTPS, FTP, SFTP, RTP, RTSP, UDP, SNMP, SMTP, DHCP (client and server), NTP (client and server), SIP (client and server) G.711 (PCMA and PCMU) and G.722														
Power Consumption	< 7 watts (typical)														
Power Supply	PoE IEEE 802.3af (variable class 2 or 3: factory setting: class 3)														
Operating Conditions	IP66/IP67 / -30°C to +60°C														
Casing Material	AISI316L Stainless Steel														
Cable Entries	2 x M25x1,5 with 1 x M25 blanking plug														
Cable Gland	1 x M25 Conduit brass gland as standard - *optional LSOH cable and cable protection glands on request														
Finish	Electro-polished														
Window	Toughened Glass Ø75 mm														
Dimensions	With sunshield (H)179 x (W)385 x (D)161 mm														
Weight	11 kg														

MODELS

SE-ATEX-IP-SCT-SS Optical lens, stainless steel casing

MOUNTING ACCESSORIES

SE-ATEX-WMKIT-T Wall mount bracket with swivel joint

SE-ATEX-WMKIT-T-PMA Pole mount adapter

SE-ATEX-IP-PTM-SS Pan & Tilt Mount Unit